

Metamark MD-MB

360gsm Mesh PVC Ink-Stop Banner Media



Product Description

This 360gsm PVC mesh banner overcomes the issue that some banners have with wind resistance, and is suitable for printers using Solvent, Latex & UV curable inks. The mesh structure allows wind to pass through while retaining 75% of the printable surface to give highly visual prints. It is still supplied with an 'ink stop' release liner to catch the ink during the printing process. It is supplied reverse wound. It can also be used for banners, and for scaffolding curtains, and is fire retardant. Fire retardant in accordance with B1.

Features & Benefits

- For Solvent, Eco Solvent, UV and Latex (300,500,700,800)
- Reverse wound, one part system.
- Fire retardant in accordance with DIN 75200.
- Used to produce high quality prints.

Face Film	
Base Fabric	Polyester
Type of Coating	PVC
Weight	270gsm
Tensile strength	1250 / 1250 N/2.5cm (warp/weft)
Tear Strength	300/310 N/2.5cm (warp/weft)
Cold Resistance	-22°C
Heat Resistance	+70°C

Finishes		
Finishes Available	MD-MB	White

Durability	
Shelf Life	1 year. (10-20°C and 50% R.H).
External weathering	<1 year (unprinted). This refers to the unprinted vinyl when installed. Refer to ink manufacturer for durability of the finished product.
Fire Rating Regulations	Fire retardant in accordance with B1. REACH Compliant.

Roll Presentation	
Roll Widths	1.37m / 1.6m
Roll Lengths	30m
SuperWide Rolls	1.9m x 50m / 2.5m x 50m / 3.2m x 60m

Printing and Handling

- Always perform a test print first. Ensure that the correct profiles and heater settings are used. Refer to www.metamark.co.uk.
- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film, ensure free from dust and static.
- The product is reverse wound, so load material accordingly.
- The weight of the banner may necessitate some slack on the unwind.
- The product is designed to be used without an overlaminates. If a liquid laminate is used it is the responsibility of the user to test.
- The durability of the finished print is dependent on the inks and printer.

MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Media and Overlaminates will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Media and Overlaminates becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

- Lunsdale • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140
- Metamark House • Genesis Business Park • Albert Drive • Woking • GU21 5RW • Tel +44 (0)1483 571111

sales@metamark.co.uk
www.metamark.co.uk