

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**Product form : Mixture
Product name : Application Fluid**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Use of the substance/mixture : Cleaning Agent/Cleaner.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Supplier**Leading Solvent Supplies Ltd
Marston Business Park Rudgate
YO26 7QF Tockwith York – North Yorkshire
United Kingdom
T +44 (0) 1423 358058 - F +44 (0)1423 358923
enquiries@leading-solvents.co.uk**Supplier information**Leading Solvents Ireland Ltd
The Courtyard Manor House
3 Church Road
Malahide – Co.Dubin
Ireland
T +353 1 845 7660**1.4. Emergency telephone number**

Emergency number : +44 (0) 1423 358058 (Office hours only)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**Flammable liquids, Category 3 H226
Serious eye damage/eye irritation, Category 2 H319
Full text of H- and EUH-statements: see section 16**Adverse physicochemical, human health and environmental effects**

Flammable liquid and vapour.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Warning

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H319 - Causes serious eye irritation.
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective gloves, protective clothing, eye protection, face protection.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	$\geq 1 - < 5$	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Docusate Sodium substance with national workplace exposure limit(s) (GB)	CAS-No.: 577-11-7 EC-No.: 209-406-4 REACH-no: 01-2119491296-xxxx	$\geq 1 - < 5$	Skin Irrit. 2, H315 Eye Dam. 1, H318
Monopropylene Glycol substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 57-55-6 EC-No.: 200-338-0	$\geq 0.1 - < 1$	Not classified
ethyl acetate substance with national workplace exposure limit(s) (GB, NL); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	$\geq 0.1 - < 1$	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Propan-2-ol substance with national workplace exposure limit(s) (DE, GB, NL)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119451558-25	< 0.1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Causes skin irritation. irritation (itching, redness, blistering). Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: redness, itching, tears. Causes eye irritation. stinging.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting. May be harmful if swallowed. May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Forms explosive air-vapour mixture.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stop leak if safe to do so.
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Cover spill with non combustible material, e.g.: sand, earth, vermiculite.
-----------------	--

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methods for cleaning up	: Take up liquid spill into absorbent material. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Storage area	: Store away from heat.
Special rules on packaging	: Keep only in original container.
Packaging materials	: Keep only in the original container in a cool, well-ventilated place away from combustible materials.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Ethanol (64-17-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethanol
WEL TWA (OEL TWA) [1]	1920 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
ethyl acetate (141-78-6)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethyl acetate
WEL TWA (OEL TWA) [1]	734 mg/m ³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	1468 mg/m ³
WEL STEL (OEL STEL) [ppm]	400 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Propan-2-ol (67-63-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA) [1]	999 mg/m ³
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Docusate Sodium (577-11-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m ³
Monopropylene Glycol (57-55-6)	
United Kingdom - Occupational Exposure Limits	
Local name	Propane-1,2-diol
WEL TWA (OEL TWA) [1]	10 mg/m ³ particulates 474 mg/m ³ total vapour and particulates
WEL TWA (OEL TWA) [2]	150 ppm total vapour and particulates
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses, Safety goggles	Dust, Fine dust	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Butyl rubber, Polyvinylchloride (PVC)	5 (> 240 minutes)	0.44		EN 374-2

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Aerosol mask	ABEK	Vapour protection, Protection for Liquid particles	EN 14387, EN 143

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: orange.
Odour	: citrus-like.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 95 – 100 °C
Flammability	: Not applicable
Oxidising properties	: Not oxidising.
Lower explosion limit	: 3.3 vol %
Upper explosion limit	: 19 vol %
Flash point	: 49 °C
Auto-ignition temperature	: > 365 °C
Decomposition temperature	: Not available
pH	: 7
Viscosity, kinematic	: Not available
Solubility	: Soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0.992
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Stable under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing agent. Strong acids.

10.6. Hazardous decomposition products

In combustion emits toxic fumes.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg bw/day
LD50 oral	8300 mg/kg bodyweight Animal: mouse, Remarks on results: other:
LD50 dermal rat	15800 mg/kg
LC50 Inhalation - Rat (Vapours)	20 mg/l/4h
ethyl acetate (141-78-6)	
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 20000 mg/kg bodyweight Animal: rabbit, Animal sex: male
LD50 dermal	> 18000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	57700 mg/l

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Propan-2-ol (67-63-0)	
LD50 oral	5840 mg/kg
LD50 dermal	13900 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	25000 mg/l/4h
Docusate Sodium (577-11-7)	
LD50 dermal rabbit	> 10000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Monopropylene Glycol (57-55-6)	
LD50 oral rat	22000 mg/kg bodyweight Animal: rat, Remarks on results: other:
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit
LC50 Inhalation - Rat	> 44.9 mg/l air Animal: rat, Guideline: other:, Remarks on results: other:
Skin corrosion/irritation	: Not classified pH: 7
Ethanol (64-17-5)	
pH	7
ethyl acetate (141-78-6)	
pH	4
Propan-2-ol (67-63-0)	
pH	5.5
Monopropylene Glycol (57-55-6)	
pH	6.5
Serious eye damage/irritation	: Causes serious eye irritation. pH: 7
Ethanol (64-17-5)	
pH	7
ethyl acetate (141-78-6)	
pH	4
Propan-2-ol (67-63-0)	
pH	5.5
Monopropylene Glycol (57-55-6)	
pH	6.5
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
Propan-2-ol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethanol (64-17-5)	
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
ethyl acetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
Docosate Sodium (577-11-7)	
NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Monopropylene Glycol (57-55-6)	
NOAEL (subchronic, oral, animal/male, 90 days)	443 mg/kg bodyweight Animal: cat, Animal sex: male
Aspiration hazard	: Not classified
Propan-2-ol (67-63-0)	
Viscosity, kinematic	3.115 mm ² /s
Monopropylene Glycol (57-55-6)	
Viscosity, kinematic	43 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

Ethanol (64-17-5)	
LC50 - Fish [1]	14.2 g/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	> 100 mg/l Leuciscus idus (Golden orfe)
EC50 72h - Algae [1]	275 mg/l (Chlorella vulgaris)
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'
NOEC chronic fish	9.6 mg/l Daphnia magna
ethyl acetate (141-78-6)	
LC50 - Fish [1]	230 mg/l Test organisms (species): Pimephales promelas
EC50 - Other aquatic organisms [1]	717 mg/l waterflea
EC50 - Other aquatic organisms [2]	3300 mg/l

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl acetate (141-78-6)	
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Propan-2-ol (67-63-0)	
LC50 - Fish [1]	9640 mg/l
EC50 - Other aquatic organisms [1]	13299 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 1000 mg/l
Docusate Sodium (577-11-7)	
LC50 - Fish [1]	49 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
Monopropylene Glycol (57-55-6)	
LC50 - Fish [1]	51600 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	51400 mg/l Test organisms (species): Pimephales promelas
EC50 72h - Algae [1]	24200 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	19300 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	19000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	19100 mg/l Test organisms (species): Skeletonema costatum

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	0.31
ethyl acetate (141-78-6)	
Partition coefficient n-octanol/water (Log Pow)	0.7
Propan-2-ol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05
Monopropylene Glycol (57-55-6)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1170	UN 1170	UN 1170	UN 1170	UN 1170
14.2. UN proper shipping name				
ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (ETHANOL)	ETHANOL (ETHYL ALCOHOL) (ETHANOL)	Ethyl alcohol (ETHANOL)	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (ETHANOL)	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (ETHANOL)
Transport document description				
UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (ETHANOL), 3, III, (D/E)	UN 1170 ETHANOL (ETHYL ALCOHOL) (ETHANOL), 3, III	UN 1170 Ethyl alcohol (ETHANOL), 3, III	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (ETHANOL), 3, III	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (ETHANOL), 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions (ADR)	: 144, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •2Y

Transport by sea

Special provisions (IMDG)	: 144, 223
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Colourless, volatile liquids. Pure ETHANOL: flashpoint 13°C c.c. Explosive limits: 3.3% to 19% Miscible with water.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A58, A180
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 144, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 144, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes

Section	Changed item	Change	Comments
1.3	Display additional SDS EU addresses	Added	
1.4	Additional information	Added	NHS 111 & EU Poison Centre

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1

Application Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.