

Metamark MD-MB

360gsm Mesh PVC Banner



Product Description

This 360gsm PVC mesh banner overcomes the issue that some banners have with wind resistance, and is suitable for printers using solvent, Latex & UV curable inks. The mesh structure allows wind to pass through while retaining 75% of the printable surface to give highly visual prints. It is still supplied with an 'ink stop' release liner to catch the ink during the printing process. It is supplied reverse wound. It can also be used for banners, and for scaffolding curtains, and is fire retardant.

Benefits

- Supplied with an 'Ink Stop' release liner to stop ink spill on printers.
- 25% Perforated area to overcome wind resistance.
- Printable using Solvent, Latex and UV curable digital inks.
- Fire retardant.

Fabric Specifications		Finishes	
Weight	360gsm	Finishes Available	MD-MB White Mesh Banner PVC
Material	Mesh PVC plus 'ink stop' release liner		
Tensile Strength	1658/1546 (Warp/Weft) N/2.5cm	Roll Presentation	
Tear Strength	214/168 (Warp/Weft) N/2.5cm	Roll Widths	1.37m / 1.60m
Type of Coating	PVC / Vinyl	Roll Lengths	30m
Cold resistance	-30°C	Durability	
Heat resistance	+70°C	Shelf Life	1 year.
Ink Stop Liner		External weathering	1 year. This refers to the unprinted vinyl when installed. Refer to ink manufacturer for durability of the finished product.
Print	Plain	Fire Rating	Fire retardant in accordance with DIN 75200 100mm/min
Weight	30 gsm nominal		
Type	White Polyurethane		

Material Handling

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

Printing Guidelines

- Suitable for use on Solvent, Eco Solvent, Latex & UV inkjet printers. Always perform a test print first.
- The product requires sufficient pinch rollers while printing.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- The durability of the finished print is dependent on the inks and printer

MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Media and Overlaminates will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Media and Overlaminates becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited