

MetaGuard 850RW

Anti Graffiti Overlaminates

Product Information Bulletin

Cleaning Notes – Initial Cleaning

Low pressure washing with warm soapy water followed by fresh water rinse; bristle brush and warm water/ simple green mix and fresh water rinse is also effective. Extreme caution should be taken so as not to lift any edges of the vinyl during this process. If a stubborn soiled area is encountered, isopropyl alcohol is recommended followed by fresh water rinse. **DO NOT USE SOLVENTS OR CAUSTIC CLEANERS** as they will leave the surface defaced when dry. Acceptable cleaning solutions and products for removing graffiti:

Product	Acceptable	Not Recommended
Soap and Water	✓	
Over the counter cleaners	✓	
Alcohol (for markers)	✓	
Petroleum Distillates (turpentine, kerosene, etc.)	✓	
Ketones (Acetone, MEK, etc.)		✓

Notes:

- All paint remover tested will degrade/dissolve adhesive.
- MetaGuard 850 Anti Graffiti coating will blister when exposed to Acetone or Lacquer thinner longer than two minutes.
- Always follow the initial paint removal with IPA or denatured alcohol.

Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.