

# Metamark Brushed Polish

## Promotional Grade



### Product Description

Metamark Brushed Polish suitable for promotional use, offering a brushed aluminium finish. The metallised film is laminated to a white PVC to allow greater adhesion than standard polyester polishes. Metamark Brushed Aluminium is top coated for screen printing and is suitable for interior applications and can be applied to flat or slightly curved surfaces.

### Features & Benefits

- Brushed finish for internal applications.
- Greater adhesion than standard polyester polishes.
- For flat or slightly curved surfaces.
- Suitable for screen printing.

#### Face Film

Face Film	PVC base with polyester overlamine
Gauge	125 micron nominal
Tensile Strength	In excess of 100N/25mm
Surface Energy	>40 dynes / cm sq.

#### Adhesive

Type	Permanent solvent-based acrylic
Adhesion to glass 20 mins	8N/25mm nominal
Adhesion to glass 24 hour	12N/25mm nominal
Perceived Tack	Medium
Shear Strength	High
Application temperature	+10°C to +50°C
Service temperature	-30°C to +110°C

#### Release Liner

Print	Plain
Weight	140 gsm nominal
Type	Clay coated kraft paper

#### Finishes

Finishes Available	MM-SBA Brushed Aluminium
--------------------	--------------------------

#### Durability

Shelf Life	1 years. (10-20°C and 50% R.H).
External weathering	Interior use.
Fire Rating	Self-extinguishing. The fire rating is a function of the substrate.
Regulations	REACH & RoHS compliant

### Application

- Suitable for interior single sided applications onto flat or slightly curved surfaces.
- Suitable for plotter use, also for contour and vinyl lettering.
- Suitable for wet application.
- Not suitable for use on compound curves.
- Not recommended for use on low energy surfaces such as polypropylene.
- The user should determine suitability of substrate.

### MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

### Metamark (UK) Limited

☐ Lunside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140

☐ Metamark House • Genesis Business Park • Albert Drive • Woking • GU21 5RW • Tel +44 (0)1483 571111

[sales@metamark.co.uk](mailto:sales@metamark.co.uk)  
[www.metamark.co.uk](http://www.metamark.co.uk)