# **MetaGuard 620**

## **Optically Clear Polyester Overlaminate**



### **Product Description**

MetaGuard 620 is a 25 micron polyester high gloss self-adhesive overlaminate suitable for cold lamination. The optically clear film offers a higher level of UV protection, maintaining the colour vibrancy of the print, and gives a low cost protection against chemicals and graffiti, and abrasion resistance, offering excellent performance at a lower cost than a PVDF overlaminate. The product is supplied on a smooth clear polypropylene liner ensuring the clarity of the solvent-based adhesive.

#### **Features & Benefits**

- Offers a higher level of UV protection.
- For use on Solvent and Eco Solvent prints.
- PVC, Phthalate and Chlorine Free.
- Excellent performance at a lower cost than a PVDF overlaminate.

Face Film		Finishes		
Face Film	High Gloss Optically Clear Polyester (PET)	Finishes Available	MG-620	Clear High Gloss
Gauge	25 micron nominal	Roll Presentation		
		Roll Widths	1.37m	
Adhesive		Roll Lengths	50m	
Туре	Permanent ultra clear pressure sensitive solvent acrylic with UV inhibitors	Presentation	Laminate outwards, on a 0.76m	
Adhesion at 20 mins	8.5N / 25 mm	Durability		
Adhesion at 24 hours	12.5N / 25mm	Shelf Life	2 years. (10-20°C and 50% R.H). 2 years. This refers to the over	
Application temperature	+4°C Minimum	External weathering		
Service temperature	-40°C to +135°C		laminate and i	not the protection that it
Release Liner		Regulations	REACH Compl	3
Print	Unprinted	9		
Type	Clear siliconised polypropylene			

## **Handling and Application**

- This product is suitable for cold lamination using a laminator.
  Apply around 30°C on the top roller to prevent silvering of the adhesive.
- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film, ensure free from dust and static.
- Refer to www.metamark.co.uk for further application guidelines.
- Suitable for use on Solvent and Eco Solvent inkjet prints on Metamark print media. Not suitable for UV prints.
- Allow the inks to cure before overlaminating, usually 24-48 hours.
  Failure to do so can cause delamination, tunnelling and shrinkage.
- Suitable for flat surfaces or single curvature only. It is not conformable, do not use on compound curves.
- Refer to www.metamark.co.uk for further application guidelines.
  The user should determine suitability of the overlaminate to the print media.



#### MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Media and Overlaminates will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Media and Overlaminates becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

## **Metamark (UK) Limited**