Metamark M7-CR-R Removable Crystal Etch for Window Manifestation



Product Description

Metamark Removable Crystal Etch is a polymeric Etch Effect Film, designed for removable window manifestation. It is ideal for use in retail, leisure, décor, office, and domestic applications. Metamark Frost can be used to create privacy, for branding, or for advertising. The film is combined with a solvent-based removable adhesive ensuring clean removal. Metamark M7-CR-R is suitable for vinyl cut graphics, and compatible with Solvent, Eco Solvent, Latex and UV printers.

Features & Benefits

- Removable Crystal Etch Effect Film.
- For window manifestation, décor and advertising.
- Solvent, Eco Solvent, Latex and UV Compatible.
- Metasure warranty up to 3 years.

Matt calendered PVC	Finishes Available	M7-CR-R	Crystal Etch
ace Film Matt calendered PVC auge 70 micron nominal			
	Roll Widths	1.22m	
Removable clear solvent-based acrylic 4N/25mm nominal	Durability	1 years. (10-20°C and 50% R.H). 3 years, Clean removable upto 6 month in vertical exposure under Northern European conditions. Class B - BS EN 13501-1:2007 Resistant to mineral oils, fats and fuels, aliphatic solvents, mild acids, salt	
6N/25mm nominal +10°C to +50°C -30°C to +110°C	Shelf Life External weathering		
	Fire Rating		
56%	Chemical Resistance		
			.g. diesel oil, gasoline,
140 gsm nominal An advanced specially treated layflat kraft paper with high internal strength	Regulations	paraffin, hydraulic oil, antifreeze, soap suds etc. REACH & RoHS compliant	
	Removable clear solvent-based acrylic 4N/25mm nominal 6N/25mm nominal +10°C to +50°C -30°C to +110°C 56% 140 gsm nominal An advanced specially treated layflat	70 micron nominal Roll Presentation Removable clear solvent-based acrylic Roll Widths 4N/25mm nominal Durability 6N/25mm nominal Shelf Life +10°C to +50°C External weathering -30°C to +110°C Fire Rating 56% Chemical Resistance 140 gsm nominal Regulations	70 micron nominal Roll Presentation Removable clear solvent-based acrylic Roll Widths 1.22m 4N/25mm nominal Durability Durability 6N/25mm nominal Shelf Life 1 years. (10-20) +10°C to +50°C External weathering 3 years, Clean to in vertical exponentiation -30°C to +110°C Fire Rating Class B - BS EN 56% Chemical Resistance Resistant to minimal fuels, aliphatic and alkali for exparaffin, hydra suds etc. 140 gsm nominal An advanced specially treated layflat kraft paper with high internal strength Regulations REACH & RoHS

- Suitable for wet or dry application.
- Apply unstressed, in particular to curves and recesses. It is not suitable for application over rivets or complex recesses.
- Not recommended to be applied between two sheets of glass
 Not recommended for use on low energy surfaces such as
- polypropylene.The user should determine suitability of substrate.

MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited